

UPAchrom 100CN (60 Hz) – Submersible Borehole Pumps From 100 mm (4 inches)



UPAchrom 100CN (60 Hz)



Applications:

- Domestic water supply, water supply systems
- General irrigation and spray irrigation systems
- Lowering of groundwater levels
- Pressure boosting
- Air-conditioning
- Fire-fighting systems
- Cooling circuits

More information:

www.ksb.com/products

Your contact:



UPAchrom 100CN (60 Hz) – Submersible Borehole Pumps From 100 mm (4 inches)

Efficiency

- Integrated check valve ensures minimum pressure loss and optimised hydraulics.
- Outstanding efficiency

Operating reliability

- Suitable for drinking water: certified to ACS
- Zero maintenance due to hydrodynamic bearings
- Motor rated for maximum pump output
- Low-noise operation
- Hermetically sealed motor
- Anti-seize check valve

Corrosion and wear resistant

- High quality pump materials and components
- Impeller made of Noryl for maximum durability

Flexibility


- Suitable for installation in narrow deep wells
- For vertical, horizontal or inclined installation
- NEMA connection

Technical data

Capacity	Up to 27 m ³ /h
Discharge head	Up to 400 m
Power rating	Up to 7.5 kW
Fluid temperature	Up to 30 °C

Automation possible with Controlmatic, UPA Control, PumpDrive

Characteristic curves UPAchrom 100CN (60 Hz)



KSB Aktiengesellschaft
 Johann-Klein-Straße 9
 67227 Frankenthal (Germany)
 www.ksb.com